




SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited

Solar Cable and Solar Connectors



- 1) Conductor: tinned copper
- 2) Insulation: flame retardant PE
- 3) Outer jacket: flame retardant PE, UV resistant.
- 4) Nominal Cross-Section: 2.5, 4, 6mm²
- 5) High quality photovoltaic solar cable
- 6) Selling to Europe and America and Australia .
Certified by TUV
- 7) Can be customized



This set include Cigar lighter, charge clip, cigar connector.
Can accept customieds
High quality photovoltaic solar cable and battery charger.



- 1) Conductor: tinned copper
- 2) Outer jacket: flame retardant PE, UV resistant.
- 3) Nominal Cross-Section: 0.5 and 1.0mm²
- 4) High quality photovoltaic solar cable and battery charger.



- 5) Can be customized



cigar lighter
Suit for 12V, 5A, 60HZ
Can be customized





SUNLINK ENERGY
Better Energy Better Life

Sunlink Energy Limited



Maximum working voltage: DC1000V
Rated Current : 25A
Flame class: UL94-V0
Shell Protection degree: IP67
Connecting cable: 2.5mm²,4mm²,6mm²
Ambient temperature range: -40~+85°C
Safety Level: class I
Insertion force:≤50N
Withdrawal force:≥50N



ABS material, UV resistance
Dimensions: 90x50x45mm
IP66, Black or White
Hold 6-12mm cable
water proof housing for fixing to the roof where the cable enter
For mounting on the roof, boat, yacht, caravan.



1) Maximum working voltage: DC1000V
2) Rated Current : 25A
3) Flame class: UL94-V0
4) Shell Protection degree: IP67
8) Connecting cable: 2.5m² 4m² 6m²
9) Ambient temperature range: -40~+85°C
10) Safety Level: class I
11) Insertion force:≤50N
Withdrawal force:≥50N



ABS material, UV resistance
Dimensions: 90x100x45mm
IP66/ Black or White ,Hold 6-12mm cable
water proof housing for fixing to the roof where the cable enter
For mounting on the roof, boat, yacht, caravan.



SUNLINK ENERGY
Better Energy Better Life


Sunlink Energy Limited



- 1.Improve sensitive of circuits and component's reliability; prolong their service life.
- 2.Insulation, shock-proof, impact resistant, working temperature range (-50 °C ~ + 230 °C).
- 3.Weathering resistance, heat resistance and corrosion-resistant.
- 4.It can resist ultraviolet, ozone, and the harmful effects of water and chemicals.
- 5.No change in physical and mechanical performance and anti-yellowing after 1,000 hour through the "double 85".

(the "double 85" means the relative temperature is 85°C, relative humidity is 85%.)

6.It can adhesive PBT, ABS, PC plastics.



crimping range:2.5,4,6mm²(26-10AWG), tool length:270mm

Solar system crimping tools for MC4

Hand crimping plier,For non-insulated open plug-type connector.MC4 solar crimper.